

Cargo Lashing Belt

DESCRIPTION & FEATURES




- **Standard:** EN 12195-2
- **Material:** Flat Woven Polyester Webbing
- **Temperature:** -40 C to 120 C
- **Construction:** Quenched and Tempered
- **Proof Load:** 2 x Lashing Capacity
- **Finish:** Cadmium Plated

Cargo Lashing Belts are available from 25mm to 100mm width & 400kg to 5,000kg for straight lashing capacity, And 800kg to 10,000kg maximum breaking capacity belts can be made as per requirement.

Safety factor of the Lashing Assembly is 2:1

Certification (MTC) provided with all flat Cargo Lashing Belt products.

Use of high grade 100% polyester material, Cadmium plated steel ratchet, hook and accessories.

Lashing Capacity (kg)	Webbing width	M.B.S (kg)	Fixed Length (m)			
400	25mm	800	0.3	400	800	800
500	25mm	1000	0.3	500	1000	1000
750	25mm	1500	0.3	750	1500	1500
750	35mm	1500	0.5	750	1500	1500
1000	35mm	2000	0.5	1000	2000	2000
1500	35mm	3000	0.5	1500	3000	3000
1500	50mm	3000	0.5	1500	3000	3000
2000	50mm	4000	0.5	2000	4000	4000
2500	50mm	5000	0.5	2500	5000	5000
3500	75mm	7000	0.7	3500	7000	7000
5000	100mm	10000	0.7	5000	10000	10000